

Payphone PP10

- Suitable for indoor use
- Highly reliable
- Coin operated
- Powered from telephone line
- Multilingual support

Features

Coin system

- 10c, 20c, 50c, \$1 & \$2
- Internal coin box with independent lock, separate from electronics compartment
- Timed local calls (optional)
- Fast power-efficient 8-position intermediate coin storage (escrow), with best-change changing algorithm

Security features

- Advanced fraud detection algorithms
- Tough ABS plastic construction
- Independent locks for electronics and coin compartments

Maintenance characteristics

- Full diagnostic and test capabilities
- Menu-driven program for field maintenance
- Display of alarms, parameters, statistics and faulty modules using the payphone test-menu
- Modular internal construction
- Remote diagnostic option from QP-SETM management system
- Failure clearance reports (option)
- Only standard tools are required

Management System Access (option)

- Payphones administered by the QP-SETM management system
- Flexible functionality creation and modification of parameters
- Fast efficient software and parameter downloading with programmable software activation date
- Payphone data recording traffic, call registers, coin collections and alarms



Telephone interface

- Standard 2-wire analogue PSTN interface
- Line-powered payphone

Operating environment

- Coated electronics
- Temperature range: 0°C to +50°C
- Relative humidity: up to 95% without condensation at 40°C

Keypad

- 12-key alphanumeric Australian standard
- Language, volume and redial function (keys independent)

Display

- 2-Line 20-character alphanumeric LCD
- Countdown timer
- Birthday reminder

Handset

- Magnetic hook mechanism

Dimensions

- Height 345mm
- Width 235mm
- Depth 170mm
- Weight 7.5kg(apx)

RRP ex GST

- Tough ABS plastic case for indoor areas **\$799**
- Payphone stand \$157
- Payphone bracket \$42